

ELAC Solano Series

ELAC The life of sound.



ELAC Solano Series

Your style, your speaker,
your music.



The basic rectangular shape of the cabinet, that is made from solid MDF, is paired with a slightly curved front baffle and provided with large radiuses. This all leads to a compact but impressive appearance.



The driver baskets of the SOLANO series are made of aluminum. Besides the attractive look and feel, aluminum ensures the mechanical stability and sets the basis for perfect sound reproduction.



The JET5 tweeter is handcrafted in Kiel / Germany. It is state-of-the-art and well-known around the whole world, if a perfect reproduction of the high frequency range is demanded.

One vision, one claim, one design ... Three models! It doesn't matter if you listen to music in a classical stereo setup or watch a movie in surround, with the BS 283 bookshelf-, the FS 287 floorstand- and the CC 281 center- speaker, the SOLANO series provides the perfect tool for any room and setup.

Compact, attractive and high-performance – the SOLANO series newly interprets the typical ELAC attributes.

All forms and materials lead to one harmonical picture. Understatement in shape and color: no focus on single elements, the focus points to the whole thing.

ELAC

Solano Series

Solano Series

Height x Width x Depth	985 x 260 x 300 mm
Weight	19.0 kg
Type	2 ½-Way, bass reflex
Woofer	2 x 150 mm Ø, AS
Tweeter	JET 5
Crossover Frequency	450 2400 Hz
Frequency Range	30 – 50000 Hz
Sensitivity	87 dB at 2.83 V/m
Suitable for amplifiers from ... to ...	4 – 8 Ω
Recommended amplifier power	40 – 300 W/channel
Nominal Peak power handling	130 W 170 W
Nominal Minimum impedance	4 Ω 3.5 Ω
Finishes	Black and White High Gloss

FS 287


Height x Width x Depth	331 x 190 x 248 mm
Weight	8.0 kg
Type	2-Way, bass reflex
Woofer	1 x 150 mm Ø, AS
Tweeter	JET 5
Crossover Frequency	2400 Hz
Frequency Range	41 – 50000 Hz
Sensitivity	85 dB at 2.83 V/m
Suitable for amplifiers from ... to ...	4 – 8 Ω
Recommended amplifier power	40 – 200 W/channel
Nominal Peak power handling	70 W 100 W
Nominal Minimum impedance	4 Ω 3.2 Ω
Finishes	Black and White High Gloss

BS 283

Height x Width x Depth	190 x 500 x 248 mm
Weight	12.0 kg
Type	2 ½-Way, bass reflex
Woofer	2 x 150 mm Ø, AS
Tweeter	JET 5
Crossover Frequency	450 2400 Hz
Frequency Range	34 – 50000 Hz
Sensitivity	87.5 dB at 2.83 V/m
Suitable for amplifiers from ... to ...	4 – 8 Ω
Recommended amplifier power	40 – 250 W/channel
Nominal Peak power handling	120 W 160 W
Nominal Minimum impedance	4 Ω 3.6 Ω
Finishes	Black and White High Gloss

CC 281

Height x Width x Depth	190 x 500 x 248 mm
Weight	12.0 kg
Type	2 ½-Way, bass reflex
Woofer	2 x 150 mm Ø, AS
Tweeter	JET 5
Crossover Frequency	450 2400 Hz
Frequency Range	34 – 50000 Hz
Sensitivity	87.5 dB at 2.83 V/m
Suitable for amplifiers from ... to ...	4 – 8 Ω
Recommended amplifier power	40 – 250 W/channel
Nominal Peak power handling	120 W 160 W
Nominal Minimum impedance	4 Ω 3.6 Ω
Finishes	Black and White High Gloss



S O L A N O
280