THE PAST
with the
Edison
Phonograph

The

PRESENT

with

RECORD CHANGER

MIRACORD 3

Enjoy the MUSIC you like by playing with

MIRACORD

the Record Changer unequalled for artistic reproduction of tone which takes normal and longplaying records indiscriminately

MIRACORD 3

the
RECORD CHANGER
operable at 3 speeds
331/8, 45, 78 rpm



According to the general demand of many lovers of music, it should be possible for them to choose the music they like, and to arrange concerts at home to their own taste and to that of their friends

*

MIRACORD is the most suitable instrument to entertain guests in Hotels, Cafés, Restaurants and, above all, in your own home

MIRACORD 3

combines the reliability, excellent finish and versatility of the earlier type of MIRACORD and is improved by the latest developments of modern record player technique

The pick-up is equipped with two separate sapphires, and in order to change from a normal record to a micro-groove (long-playing) record, it is only necessary to switch from one needle to the other without any changing of either needle or system

A new overload-coupling prevents any damage to the instrument arising from wrong handling

The instrument will take from 8 to 12 records of either 10" or 12" Ø, and these can be played in any order desired

A record can be automatically repeated, interrupted, or the instrument will change over to the next record. MIRACORD is also capable of pausing automatically between the records

Owing to the extremely light weight of the pick-up, records will now last much longer

The instrument can also be used as any normal type of gramophone

Technical data of MIRACORD 3

Power Supply:
Alternating current 50 cycles
voltages 110 and 220 volts
Speed:
adjustable as required by records,
to 78 rpm for normal records or
to either 45 or 33¹/₃ rpm
for micro-groove records

The pick-up:
has a
duplex crystal system
for normal or micro-grooverecords.
Pressure on record:
10 gr. appr.
Frequency range:
from 30 to 14,000 cycles

Dimensions:
Width: 16"
Depth: 13"
Height
above mounting plate: 5.5"
Height
below mounting plate: 3.1"